

Application No. 10/533,257  
Amendment Dated June 29, 2009  
Reply to Office Action of April 1, 2009

**Amendments to the Drawings:**

Attachment: Replacement Sheets

The drawings are amended. Figure 1 is amended to delete section line II-II. Figure 2 is deleted and Figures 3a, 3b, 4a, 4b are renumbered 2a, 2b, 3a, 3b, respectively. The line quality is also improved.

### **REMARKS**

The Office Action mailed April 1, 2009 has been carefully considered by Applicant. Reconsideration is respectfully requested in view of the foregoing amendments to the claims, drawings and specification, and the remarks that follow.

#### **Allowable Subject Matter**

Claims 1-20 are indicated to be allowable if rewritten or amended to overcome the rejections under Section 112, second paragraph, set forth in the Office Action.

#### **Drawings**

The drawings are objected to because of faded cross-hatching. Herewith, the Applicant submits amended drawings having darkened lines for cross-hatching. Figure 2 has been cancelled from the set of figures. The section line II-II in Figure 1a has also been deleted. No new matter is added by these changes.

The drawings are now believed to include non-faded cross-hatching. As such, withdrawal of the objection to the drawings is respectfully requested.

#### **Specification**

The disclosure has been objected to because of several language informalities, which are hereby corrected in the enclosed amended specification. Further changes have also been made to delete references to Figure 2 and section line II-II from the specification. No new matter is added by these changes.

Withdrawal of the objection to the specification is thus respectfully requested.

#### **Claim Rejections Under 35 U.S.C. §112**

Claims 1-20 have been rejected under 35 U.S.C. §112, second paragraph, as being indefinite. By the present Amendment, the claims are amended to place the same in conformance with U.S. claim practice and to remove the indefiniteness noted by the Examiner in paragraph 3 of the Office Action.

The Examiner asks "does the device or the container include the partition wall (claim 1, line 4)?" Claim 1 amended to clearly recite that the device comprises the partition wall.

The Examiner asks "how is the extension of the maneuvering end formed as the sealing member (claim 2)?" It is believed that the Examiner intended to refer to claim 3, which is amended to state that the valve sealing member forms an extension of the maneuvering end.

The Examiner indicates "there is no structure set forth defining the bracing rings or buckle locators." Firstly, the Examiner's statement regarding the bracing rings is nonsensical. The term "rings" is itself a structural term. The term "bracing" defines the function of that structure. There is no indefiniteness with respect to the bracing rings. Claim 11 is amended to further define the buckle locators as being "axially extending corrugations or folds capable of yielding a certain resistance to radial deflection of the membrane". Claim 11 is therefore believed definite.

The Examiner indicates "it is unclear how the sealing member is connected to a spring element to urge it towards the opening." It is believed the Examiner is referring to claim 16, which has now been cancelled, thus rendering the Examiner's point moot.

The Examiner asks "wherein the preamble sets forth the device as the claimed invention and the container is not part of the claimed invention, how does one determine the underpressure condition?". The Applicant does not understand the meaning behind the Examiner's question and it is respectfully asked that she rephrase the question and provide further detail. Firstly, determination of an "underpressure condition" is not recited in the language of the claims. As such, the Applicant is not entirely sure to what the Examiner is referring. Further, claim 1 has been amended to state that one side of the membrane is structured for receiving an underpressure which, together with the ambient pressure, creates a differential pressure across the membrane. This recitation is believed definite. If there are any further questions regarding this matter, the Examiner is encouraged to contact the undersigned attorney by telephone.


Application No. 10/533,257  
Amendment Dated June 29, 2009  
Reply to Office Action of April 1, 2009

Conclusion

The present application is thus believed in condition for allowance. Such action is respectfully requested.

Respectfully submitted,

ANDRUS, SCEALES, STARKE & SAWALL, LLP

By   
Peter T. Holsen  
Reg. No. 54,180

Andrus, Sceales, Starke & Sawall, LLP  
100 East Wisconsin Avenue, Suite 1100  
Milwaukee, Wisconsin 53202  
Telephone: (414) 271-7590  
Facsimile: (414) 271-5770

AN OPENING-FORCE-MAXIMIZING DEVICE OF AN UNDERPRESSURE-  
ACTIVATED VALVE FOR A DRINKING CONTAINER

CROSS REFERENCE TO RELATED APPLICATION

The present application is the U.S. national stage  
5 application of International Application PCT/NO2003/000361,  
filed October 29, 2003, which international application was  
published on May 13, 2004 as International Publication WO  
2004/039690. The International Application claims priority  
of Norwegian Patent Application 20025193, filed October 29,  
10 2002.

BACKGROUND OF THE INVENTION

The present invention relates to an opening-force-maximizing  
device of an underpressure-activated, self-adjusting valve  
for a drinking container. The container may contain a  
15 pressurized or non-pressurized soft drink or other liquefied  
article of food. The device is intended for use in connection  
with a drinking spout for the container.

Underpressure-activated devices for automatic opening of drinking valves are known from previous patent publications, including US 6.290.090. The opening mechanism according to US 6.290.090 includes a pressure-responsive membrane for activating a valve of a drinking can containing a carbonated, pressurized drink. The valve allows for spill-free consumption of the contents of the can. The membrane, which forms a ~~manoeuvring~~maneuvering member of the drinking valve, is concentric and formed approximately planar about the longitudinal axis of the drinking can, said plane being perpendicular to the longitudinal axis. The membrane is also fixedly attached along its entire circumference. A flow-through stay, which is a part of a sealing member of the valve, connects the membrane to the sealing member, which opens or closes an outlet opening of the can. The membrane is activated when a user sucks an underpressure on one side of it, thereby creating a differential pressure across the membrane. The differential pressure generates a pressure force moving the membrane and the sealing member in an axial and valve-opening direction. As the activating surface of the membrane is larger than the valve surface covering the outlet opening, a valve opening force is produced and transmitted, which may be sufficiently large for the valve to open, even at a given overpressure in the can.

To use this type of membrane structure for opening a valve of a drinking container of pressurized liquid, involves several weaknesses:

Inasmuch as the peripheral regions of the planar membrane according to US 6.290.090 are secured and thereby may move insignificantly during said pressure influence, mainly the central portion of the membrane is axially moveable. The

effective, pressure-responsive membrane surface area thus is reduced, causing relatively insignificant force to be transmitted to the valve sealing member. Increasing the area of the membrane in the radial direction may solve this

5 problem. However, such a solution is not possible when used in standard bottle caps, in which the membrane diameter is limited by the cap diameter. The user may, however, compensate for a reduced, effective membrane area and attenuated pressure force by increasing the suction force on  
10 the membrane. However, the user must use a disproportionately large suction force, especially during incipient opening of the valve when the drinking can is pressurized. This valve device may not be perceived as being very functional and user-friendly.

15 Moreover, this membrane structure is not provided with bracing elements that concentrate and transmit the membrane pressure force to the valve sealing member.

Nor is the membrane structure arranged with any opening-force-maximizing device that limits the incipient suction  
20 force required during valve-opening of a pressurized drinking can.

The sealing member is also placed on the downstream side of the can's outlet opening, allowing it to open automatically at a given overpressure in the drinking can. Its liquid  
25 contents thus will flow out of the can unintentionally. If this unintended effect is to be avoided, the valve must only be used on drinking cans containing non-carbonated drinks, which defies the object of the valve device according to US 6.290.090. Possibly, the membrane must be reinforced or  
30 braced to avoid unintended outflow when the liquid contents

is pressurized, whereby the user must supply additional suction force to the membrane. However, this further weakens the functionality and user-friendliness of the valve.

In connection with ordinary bottle caps and carbonated  
5 drinks, the main problem of this membrane structure therefore lies in its effective membrane area being too small to provide sufficient valve opening force, especially in the opening phase of the valve. For this reason, the valve device according to US 6.290.090 will be experienced as not being  
10 very functional and not being very user-friendly.

#### SUMMARY OF THE INVENTION

The object of the present invention is to remedy the above-mentioned disadvantages of prior art.

The object is achieved by means of the features disclosed in  
15 following description and the subsequent claims.

The present valve device is special in that it is arranged to transmit the largest opening force to the valve sealing member during the incipient phase of the valve-opening, even if the user employs a moderate underpressure to activate the  
20 valve device. This effect makes the valve user-friendlier, especially when the sealing member must open against an overpressure in the drinking container. When consuming carbonated drinks, for example, the pressure at the opening instant will always be larger than that of the following  
25 drinking phase. The valve device is also advantageous to persons having little suction force, including small children and some categories of disabled and sick persons.



In connection with a drinking spout for the container, particular embodiments of the valve device also provide great advantages during production thereof, cf. the following exemplary embodiments.

5 In principle, the valve device according to the invention operates by utilizing a tensile force arising along a sleeve-like body in the form of a membrane, and which is transmitted to the valve sealing member. The tensile force arises when the membrane is supplied a differential pressure and is  
10 deflected perpendicularly from its longitudinal direction. This causes an axial contraction of the membrane and a resulting axial movement of the sealing member.

The principle intended to be utilized in the present invention, and which will be described below, is best  
15 illustrated by the following analogy of a rope extended between its two end points. Said membrane deflection will proceed in approximately the same way as the extended rope will deflect perpendicular to its longitudinal direction when subjected to a lateral force "S". The rope analogy  
20 illustrates the forces utilized in the present valve device. The lateral force "S" on the rope results in a reactive tensile force "F" along the deflected rope. The tensile force "F" is transmitted to the attachment ends of the rope and is many times larger than the applied lateral force "S". By  
25 fixing one end of the rope, the tensile force "F" may be used to move the other end of the rope in the longitudinal direction (axial direction) of the rope. This effect is analogous to the effect of the present membrane structure. During the deflection, the tensile force "F" at either  
30 attachment end may be decomposed into an axial force component " $F_a$ ", which is parallel to the original axial

direction of the rope prior to deflection, and a shear component " $F_s$ ", which is perpendicular to said axial direction. A deflection angle " $a$ " existing between the original axial direction of the rope and its direction when deflected, will increase with increasing deflection. When the angle " $a$ " increases, the magnitude of each force component " $F_a$ " and " $F_s$ " will change in accordance with general geometric considerations, hence in accordance with trigonometric functions. The force component " $F_a$ " thus becomes a function of  $(\cos "a")$ , whereas the shear component " $F_s$ " becomes a function of  $(\sin "a")$ , both functions being non-linear. The axial component " $F_a$ " is at its largest when the deflection angle " $a$ " is small, i.e. during the incipient phase of the deflection of the rope. The opposite relation applies to the shear force  $F_s$ . The deflection also results in a non-linear axial contraction of the rope. Under the circumstances depicted herein, the axial movement (contraction) of the rope will be the least during the incipient phase of the deflection, after which the axial movement increases.

Corresponding force and contraction considerations also are utilized in the present membrane structure. Inasmuch as the axial component " $F_a$ " transmits and contributes a valve opening force to the sealing member, the maximum opening force will be transmitted during the incipient phase of the membrane deflection, when the deflection angle is at its smallest. This implies that the membrane structure causes a large opening force and small sealing member movement during incipient opening of the valve, whereas the force decreases and the sealing member movement increases afterwards. By utilizing the rope principle, the opening force of the valve may be increased considerably relative to existing valve

opening mechanisms, and particularly at the onset of the sucking/drinking process when the overpressure in a carbonated drink container is at its largest.

In its position of use, the present valve device is connected  
 5 to an outlet opening, for example a bottle opening, of the drinking container. Among other things, the valve device includes a partition wall covering and pressure-sealingly enclosing said outlet opening and separating the interior of the drinking container from the ambient environment. The  
 10 partition wall is provided with a wall opening, the upstream side of which is in pressure-sealing contact with the valve sealing member when in a position of rest.

The valve device also includes a peripherally continuous membrane arranged about an axis onto said partition wall and  
 15 through the wall opening. Inasmuch as the membrane is arranged with an axial extent relative to said axis, hereinafter referred to as a valve axis, it is provided with two axial termination ends, comprising one attachment end and one ~~manoeuvring~~maneuvering end. In position of use, the  
 20 attachment end is fixedly connected to said partition wall, whereas the ~~manoeuvring~~maneuvering end is movable and placed at an axial distance from the attachment end. In a tensile-force-transmitting manner, the ~~manoeuvring~~maneuvering end is arranged to a valve sealing member capable of opening or  
 25 closing said partition wall opening. The ~~manoeuvring~~maneuvering end may be connected to either a sealing member or an extension of the ~~manoeuvring~~maneuvering end formed as a sealing member. Via its support, the sealing member is arranged axially movable relative to the wall  
 30 opening. This membrane structure thus forms said sleeve-like membrane enclosing the valve axis and the sealing member, and

the sleeve-like membrane for example being of a cylindrical and/or conical shape.

To prevent undesired access to the contents of the drinking container before consumption, the sealing member and an edge  
5 of the wall opening may be connected via a breakable seal that is broken upon first-time movement of the sealing member. Breaking such a seal, however, requires an additional force to be applied to the sealing member during incipient opening of the valve, the operation of which the present  
10 valve device is well suited for providing.

The present membrane is activated by means of a user sucking an underpressure on one side of the membrane, as with the membrane according to US 6.290.090. Also, the present  
15 membrane is pressure-balanced against the ambient pressure of the container. The membrane activation thus may be carried out independently of the pressure inside the container. This distinguishes the present valve from, for example, a flap valve, which is pressure-balanced against the container pressure. Also, the drinking container is pressure-balanced  
20 against the ambient pressure.

The shape and method of attachment of the present membrane differ substantially from those of the device according to US 6.290.090. The differences significantly affect the opening force sequence during opening of the valve, and  
25 particularly during its incipient opening.

As mentioned, the membrane according to US 6.290.090 is of an approximately planar form and is attached along its circumference. When in position of rest, it therefore has no longitudinal extent axially. The valve-opening tensile force

transmitted to the sealing member when activating the membrane, thus extends in the same direction as that of the differential pressure force on the membrane, i.e. perpendicular to the membrane. This causes the above-mentioned disadvantages, including weak opening force acting on the valve sealing member.

Inasmuch as the present membrane structure is provided with longitudinal extent axially, this implies that the effective, pressure-responsive area of the membrane may be increased by means of increasing the longitudinal extent of the membrane, but without increasing its radial extent. Thereby, the pressure force on the membrane may be increased without expanding the membrane radially. This is favourable in standard bottle caps, in which the radial extent of the membrane is limited by the cap diameter.

As a consequence of the present membrane structure, the perpendicular differential pressure onto the membrane is converted to a longitudinal valve opening force aimed in the general longitudinal direction of the sleeve-like membrane. Thereby, the opening force is essentially parallel to the longitudinal direction of the membrane, but approximately perpendicular to the direction of the differential pressure force.

For each axial section through the membrane, the longitudinal direction of the membrane is defined between its attachment end and its ~~manoeuvring~~maneuvering end. In a cylindrical construction, the longitudinal extent of the membrane is parallel to the valve axis, whereas in a conical construction, for example, the membrane is not parallel to the valve axis. In the latter case, the longitudinal extent

will provide at least one axial component and at least one radial component. Although the longitudinal direction of the membrane, hence the direction of the valve opening force, is not parallel to the valve axis, it is the axial component of the opening force parallel to the valve axis that provides axial movement of the sealing member relative to said wall opening.

Depending on the desired valve functionality and valve geometry, the membrane deflection may be carried out by allowing the membrane to deflect inwards towards the valve axis, or outwards from the valve axis. This is achieved either by arranging the membrane to deflect radially inwards towards the valve axis, the membrane thus assuming the form of an hour-glass, or by arranging the membrane to deflect radially outwards from the valve axis, the membrane thus swelling like a balloon. Thereby, said underpressure must be applied to the inside or the outside of the membrane sleeve, respectively. When an expandable membrane is used, its mid portion is preferably shaped as a longitudinal bellows having axially extending folds of a depth adapted for the desired degree of expansion.

Moreover, in order to transmit the largest incipient opening force in the longitudinal direction of the membrane construction and onwards to the valve sealing member, the sleeve-like membrane body must be arranged with a maximum longitudinal extent (measured along the valve axis) when at rest in its inactive position. Being at rest corresponds to said rope being in its extended and secured state before being subjected to the lateral force "S".

Incipient maximum force transmission is achieved only if said rope is arranged in a manner inhibiting axial stretching, the length of the rope thereby being insignificantly extensible at the relevant tensile loads. This property is provided  
5 through choice of material, dimensioning and/or structure of the relevant rope. Thus, highly elastic or plastically deformable ropes, including elasticity-ropes and rubber bands, are poorly suited. However, all ropes are elastic to some degree and will be subjected to a certain elastic  
10 stretching when subjected to tensile loads. The desired effect is therefore achieved by choosing a rope that exhibits insignificant elastic stretching when subjected to the tensile load caused by the relevant side force "S".

Correspondingly, the present membrane must be arranged in a  
15 manner inhibiting axial stretching, the longitudinal extent of the membrane thereby being insignificantly extensible axially at the relevant tensile loads caused by said differential pressure acting on the membrane. This property is provided through skilled choice of material, dimensioning  
20 and/or construction of the relevant membrane. The chosen membrane must therefore be able to exhibit insignificant elastic longitudinal stretching at said tensile loads. For this reason, the membrane may not be easily stretchable in the axial direction. Consequently, it also may not be  
25 provided with one or more membrane-length-promoting deformations, for example concentric corrugations or folds, which allow axial extension of the membrane under the influence of an axial tensile force. If so, the incipient tensile force will extend the membrane material or its  
30 deformation zone(s) instead of being transmitted to the sealing member for movement thereof.

To be able to deflect radially, the membrane must be radially flexible and therefore be able to deflect in a radial direction relative to the valve axis. Therefore, the membrane must have little resistance to radial deformation. In order to provide the membrane with a desired deflection profile upon activation, the membrane may be provided with one or more bracing peripheral rings spaced apart between the attachment end and the ~~maneuvering~~maneuvering end of the membrane. For this purpose, the membrane may also be arranged with one or more buckle locators, for example weak corrugations, which localize desired deflection regions of the membrane.

The membrane may also be braced axially by being arranged with a certain axial rigidity, for example by means of axially extending corrugations or folds, yielding a certain resistance to radial deflection. Thereby, the membrane may exert a firm closing force on the sealing member when the membrane is at rest in its inactive position, in which the valve is in its closed position. If the membrane also is provided with an adapted elastic rigidity through appropriate choice of membrane material and geometric shape, an activated membrane will also possess sufficient stored energy in the form of resiliency to be able to push the sealing member back into its valve-closing position when the underpressure acting on the membrane ceases. Thus, the membrane may be provided with one or more axial braces. For this purpose, the membrane, when viewed in cross-section, may also be arranged into a hexagonal shape, a star shape, a wave shape etc., which has an axial bracing effect. Alternatively, the sealing member may be connected to a separate spring element urging the sealing member pressure-sealingly towards said opening in



the partition wall of the valve device when the membrane is in its position of rest.

The membrane may also be formed asymmetrically about its valve axis, including its attachment end and/or  
 5 ~~manoeuvring~~maneuvering end. It may also have an asymmetrically positioned sealing member arranged thereto.

Preferably, the membrane is formed of a thin-walled plastics material. It may also be formed of different types of plastics materials suitably combined to achieve suitable  
 10 properties in the relevant membrane structure.

#### BRIEF DESCRIPTION OF THE DRAWINGS

In the following, different exemplary embodiments of the invention will be shown, in which:

Figure 1a shows a conically shaped membrane in its position  
 15 of rest while an associated sealing member is placed in a valve-closing position, the membrane being arranged for outward radial movement upon underpressure-activation;

Figure 1b shows the membrane according to Figure 1a in an activated and expanded position while the sealing member is  
 20 placed in its valve-opening position;

~~Figure 2 shows a radial section along section line II-II of the inactive membrane shown in Figure 1a;~~

Figure ~~3a~~2a shows a conically shaped membrane in its position of rest while an associated sealing member is placed in a

valve-closing position, the membrane being arranged for inward radial movement upon underpressure-activation, and the membrane being provided with buckle locators providing the membrane with a desired deflection profile upon activation  
5 (buckle locators not shown);

Figure ~~3b2b~~ shows the membrane according to Figure 3a in its activated and radially contracted position while the sealing member is placed in a valve-opening position;

Figure ~~4a3a~~ shows a partly cylindrically and partly conically  
10 shaped membrane in its position of rest while an associated sealing member is placed in a valve-closing position, the membrane being arranged for inward radial movement upon underpressure-activation, and the membrane being provided with a bracing peripheral ring that divides the membrane into  
15 said cylindrical and conical portions; and

Figure ~~4b3b~~ shows the membrane according to Figure ~~4a3a~~ in its activated and radially contracted position while the sealing member is placed in a valve-opening position, said cylindrical membrane portion causing the largest radial  
20 buckling and the largest axial contraction.

Furthermore, the figures may be somewhat distorted.

#### DETAILED DESCRIPTION OF THE INVENTION

Figure 1a and Figure 1b show a bottle 2 with a bottle opening 4, to which is connected an opening-force-maximizing valve  
25 device according to the invention. A pressure P3 exists inside the bottle 2, whereas the bottle is surrounded by an

atmospheric pressure P1. Among other things, the valve device includes a conical partition wall 6 with a peripheral circumferential rim 6a and a wall opening 8, the partition wall 6 being connected to the bottle 2 and pressure-sealingly enclosing the bottle opening 4 via a ring gasket 10.

This valve device also includes a peripherally continuous conical membrane 12. The membrane 12 is arranged external to the bottle 2 and is concentric about a valve axis 14 onto the partition wall 6 and through the valve opening 8. Moreover, all valve components in this and subsequent exemplary embodiments are concentric about the valve axis 14. Further, the membrane 12 has an axial extent relative to the valve axis 14, whereby the membrane 12 has two axial termination ends, comprising an attachment end 12a and a ~~manoeuvring~~maneuvering end 12b. The attachment end 12a, which in this example consists of a peripheral circumferential rim, is connected to the outside of the circumferential rim 6a of the partition wall 6. The attachment end 12a and the circumferential rim 6a are attached to the bottle opening 4 by means of a drinking spout 16 with a drinking opening 17 and an internally threaded base 18 matching external threads 20 on the bottle 2. The ~~manoeuvring~~maneuvering end 12b, which is movable, is placed at an axial distance from the attachment end 12a, and it is connected in a tensile-force-transmitting manner to an axially movable valve sealing member 22. In this exemplary embodiment, the sealing member 22 forms an extension of the ~~manoeuvring~~maneuvering end 12b being formed as a sealing member 22. This provides for great ~~production~~-technical advantages when producing the valve device ~~is~~ in connection with the drinking spout 16 for the bottle 2. Thereby, the membrane 12 and the sealing member 22 may be produced in one valve piece and of the same material,

which simplifies the production process and provides for economic advantages. In terms of production~~Production-~~  
~~technically speaking~~, this one valve piece may possibly be delivered assembled together with the partition wall 6, which  
 5 further simplifies the subsequent assembling of the valve device and the associated drinking container.

The sealing member 22 consists of an axially extending, flow-through stay 24. One end of the stay 24 is shaped and widened like a valve head 26 placed on the inside of the partition  
 10 wall 6, and bearing pressure-sealingly against a valve seat 28 in the partition wall 6 when at rest, cf. Figure 1a. The other end of the stay 24 is formed with an external guide sleeve 30 being open in the direction of the valve seat 28, and being connected to the membrane 12. At its wall opening  
 15 8, the partition wall 6 is shaped as an axial guide collar 32, which the guide sleeve 30 encloses in a complementary manner, whereby they form an axial guide for the sealing member 22. A peripheral region of the stay 24 is also provided with ~~through-going~~through slots 34 for fluid outflow  
 20 when the present valve is open. When the membrane 12 is in its position of rest, the slots 34 are positioned directly opposite the guide collar 32, cf. Figure 1a, whereas they are displaced axially into the bottle 2 when the membrane 12 is activated, cf. Figure 1b.

25 The membrane 12 is shaped as a longitudinal, conical bellows with axially extending folds 36 distributed along its circumference; cf. Figure 1a. ~~In a radial section through a mid portion of the membrane 12 when in its position of rest, Figure 2 shows individual membrane folds 36, cf. section line II-II in Figure 1a.~~  
 30

The membrane 12 is also arranged to move radially outwards from the valve axis 14, as shown in Figure 1b. As a consequence of this membrane structure, a suction chamber 38 exists between the membrane 12 and said drinking spout 16.

5 The membrane 12 is activated when a user sucks an underpressure  $P_2$  in the suction chamber 38. Among other things, the underpressure  $P_2$  must be sufficiently large to overcome the repose resistance of the membrane 12, the repose resistance representing a given elastic stiffness of the  
10 membrane 12 when at rest and resulting from the membrane material, dimensioning, shape and construction thereof. When the underpressure  $P_2$  overcomes the repose resistance, the membrane 12 contracts axially, moving the sealing member 22 inwards in the bottle 2, whereby the valve opens. Thereby, a  
15 maximum opening force is transmitted to the sealing member 22 during incipient opening of the valve. Simultaneously, atmospheric pressure  $P_1$  is admitted into a pressure equalizing chamber 39 via suitable vents, the chamber 39 being located between the partition wall 6 and the membrane  
20 12.

In Figures 1a and 1b, said vents consist of a suitable number of radial venting grooves 40 formed on the outside of the circumferential rim 6a of the partition wall 6. Corresponding radial venting grooves 42 are formed on the inside of the  
25 circumferential rim 6a for admitting air into the interior of the bottle 2, cf. Figure 1b. Alternatively, said ring gasket 10 is provided with corresponding grooves (not shown) for air admission purposes. The grooves 40, 42 must be sufficiently narrow in order not to affect the sealing function around the  
30 bottle opening 4, but they must be deep enough to allow atmospheric air pressure  $P_1$  to pass through them.

The inside of the partition wall 6, at its circumferential rim 6a, is also provided with a concentric, axially projecting sealing edge 44. The ring gasket 10 may pressure-seal against the sealing edge 44 whenever the pressure P3 within the bottle 2 equals or exceeds the ambient pressure P1. For this purpose, the ring gasket 10 is provided with an elastically biased inner lip edge 46 bearing pressure-sealingly, when at rest, against the sealing edge 44. In contrast, when the pressure P3 in the bottle 2 becomes lower than the ambient pressure P1, for example when consuming fluid from the bottle 2, the ambient pressure P1 will force air through the grooves 42 and push the lip edge 46 away from the sealing edge 44, thereby admitting air into the bottle 2.

A second embodiment of the valve device according to the invention is shown in Figure 3a2a and Figure 3b2b. Wherever possible, the same reference numerals have been used for like parts with the addition of the prefix "1". Also this valve device is provided with a peripherally continuous, conically shaped membrane 112, which, as opposed to the previous membrane 12, is arranged for inward radial movement upon underpressure-activation. Therefore, the suction chamber 138 is placed on the inside of the membrane 112, whereas its pressure equalizing chamber 139 is placed on the outside thereof. The partition wall 106 is cylindrically shaped to allow the membrane 112 to move radially when activated. The admission of air into the suction chamber 138 takes place through radial venting grooves 140 formed on the outside of the attachment end 112a of the membrane 112. An axially movable sealing member 122 is connected to the ~~manoeuvring~~maneuvering end 112b of the membrane 122. The sealing member 112 consists of a axially extending, flow-through stay 124, one end thereof being shaped as a widened

valve head 126 that, when at rest and when the membrane 112 is inactive, bears pressure-sealingly against a cam-shaped valve seat 128 on the inside of the partition wall 106, cf. Figure 3a2a. Moreover, the wall opening 108 of the partition wall 106 is shaped as an axially extending, widened collar 132, the internal diameter of which is larger than the external diameter of slots 134 of the stay 124. At rest, in their valve-closing position, the slots 134 are placed directly opposite the collar 132, forming connecting openings between said suction chamber 138 and a drinking opening 117, cf. Figure 3a2a. At its other end, the stay 124 is formed with an external guiding edge 150 being axially movable within a circular guide 152 formed internally in the drinking opening 117 of the drinking spout 116. When moving axially, the stay 124 is supported laterally by the guide 152 and by the cam-shaped valve seat 128. In said position of rest, an elastically biased, inner lip edge 146 of a ring gasket 110 is also pressed pressure-sealingly against the partition wall 106. When the valve opens, the sealing member 122 is pushed axially inwards into the bottle 2, whereby fluid may flow out through the pushed-in slots 134. During fluid consumption, the ambient pressure P1 will force air through venting grooves 142 on the inside of the circumferential rim 106a and push the lip edge 146 away from the partition wall 106, cf. Figure 3b2b, thereby allowing air to pass and enter into the bottle 2.

A third embodiment of the valve device according to the invention is shown in Figure 4a3a and Figure 4b3b. Wherever possible, the same reference numerals have been used for like parts with the addition of the prefix "2". Also this valve device is arranged for inward, radial movement and operates essentially in the same manner as the previous valve device.

The device according to Figure 4a3a and Figure 4b3b, however, is provided with a membrane 212 consisting of a cylindrical membrane portion 260 proximate its attachment end 212a and a conical membrane portion 262 proximate its

5 ~~manoeuvring~~maneuvering end 212b, cf. Figure 4a3a. To provide the membrane 212 with a desired deflection profile upon activation, it is provided with a peripheral bracing ring 264 positioned between said membrane portions 260, 262. Figure 4b3b shows the membrane 212 activated and deflected inwards  
10 towards the valve axis 14. The cylindrical membrane portion 260 is deflected the most and provides the largest axial membrane contraction. The device is arranged with an internal suction chamber 238 and an external pressure equalizing chamber 239 connected to the ambient pressure P1 via  
15 external, radial venting grooves 240 in its attachment end 212a. Also this device comprises a cylindrical partition wall 206 having, among other things, an axially extending collar 232, a sealing member 222 with a stay 224 essentially similar to the stay 124, and a ring gasket 210 corresponding to the  
20 ring gasket 110.

Although all exemplary embodiments are described for use on a bottle, it must be stressed that the valve device according to the invention may be adapted to all types of drinking containers, and to both pressurized and non-pressurized  
25 fluids.